

Product Specifications



Part Number: HS-0.75x48LD
Light Duty 0.75 in x 4.0 ft sticks
Light Duty Heat Shrink

Dimensions

Length: 4.0 ft
Diameter: 0.75 in
Shrink Ratio: 3 to 1
Box of 100 4' long sticks

General Specifications

Highly Flame Retardant
Operating Temp: -55°C to +110°C
RoHS compliant
Meets SAE-AMS-DTL-23053/4
Dual Wall Adhesive Lined Heat Shrink
Excellent Sealing and Insulation Properties
UL Listed and UV Resistant

Mechanical Specifications

Property of Jacket

Tensile strength: ASTM D 2671 ≥ 13 Mpa
Ultimate elongation: ASTM D 2671 $\geq 400\%$
Longitudinal shrinkage: UL 224 @ 0 to -10%
Heat aging, tensile strength, ultimate elongation: 158°C, 168 hrs. > 11 Mpa, $> 300\%$
Flammability: VW-1, PASS.
Volume resistance: ASTM D 2671 $> 10^{10}$ Ω.cm

Property of Adhesive

Ring Ball Soft Point: ASTM E28 $95 \pm 5^\circ\text{C}$

Product Application

To be used as a weather proofing item for sealing connections against water intrusion.

