

Product Specifications



Part Number: HS-0.25-CLR-SP
100' CLEAR Spool 1/4" Heat Shrink
No Adhesive

Dimensions

100' spool 1/4" Diameter Clear Heat Shrink
Boxes of 10 Spools

General Specifications

Operating Temp: -55°C to +105°C
Min Shrink temp: 70°C
Min Full Recovery Temp: 95°C
Shrink Ratio 2:1
RoHS compliant
Cross Linked Non-Adhesive Lined Polyolefin
No Adhesive

Mechanical Specifications

Tensile strength: ASTM D 2671 >12 Mpa
Ultimate elongation: ASTM D 2671 >400%
Longitudinal shrinkage: UL 224 0 ± 5%
Eccentricity: ASTM D 2671 <30%
Heat aging, tensile strength, ultimate elongation: 136°C, 168 hrs.>11 Mpa, >200%
Flammability: Flammable
Voltage withstand: ASTM D 2671/AC 2500V, 1 min. No Breakdown
Volume resistance: ASTM D 2671 >10¹²Ω.cm
Copper stability: UL 224 Pass
Copper corrosion: UL 224 No Corrosion

Product Application

To be used as a weather proofing item for sealing connections against water intrusion. Clear for inspection issues on site.

